



(19)

(11) Publication number: **62280067 A**

Generated Document.

## PATENT ABSTRACTS OF JAPAN

(21) Application number: **61125132**

(51) Intl. Cl.: **B41M 5/00 B32B 5/18 B32B 7/02**

(22) Application date: **30.05.86**

(30) Priority:

(43) Date of application publication: **04.12.87**

(84) Designated contracting states:

(71) Applicant: **CANON INC**

(72) Inventor: **CHIBA MASAHIRO  
HIKUMA MASAHIKO  
MOROHOSHI NAOYA**

(74) Representative:

### (54) **RECORDING MATERIAL**

(57) Abstract:

**PURPOSE:** To obtain excellent ink absorptivity and fixability, by providing an ink transport layer and an ink-holding layer, and setting the melting temperature of the ink transport layer to be not lower than a specified temperature.

**CONSTITUTION:** A recording material comprises a base as a support, an ink-holding layer provided on the support to absorb or trap a recording liquid or a recording agent, and an ink transport layer provided on the ink-holding layer to directly accept the recording liquid but have a liquid-passing property so that the recording agent can not remain therein. When the melting temperature of the ink transport layer is set to be at least 50°C, the layer has excellent coated film strength, does not show surface tackiness or blocking even

under high-humidity conditions, and images with clear density can be obtained. The ink transport layer comprises particles non-dyeable with the recording agent and a binder. The non-dyeable particles may be at least one kind of particles of an organic resin such as a thermoplastic resin and a thermosetting resin or a powder of an inorganic pigment treated to be nonporous. The binder may be polyvinyl alcohol, an acrylic resin, a styrene-acryl copolymer or the like. The recording material has excellent ink absorptivity, free from disorder in images, and capable of being used for high-speed recording.

COPYRIGHT: (C)  
1987,JPO&Japio